



# PRODUCT INFORMATION

## IMPORTANT SAFETY INFORMATION

It is the sole responsibility of the purchaser of MATRIX products to instruct all individuals, whether they are the end user or supervising personnel on proper usage of the equipment.

It is recommended that all users of MATRIX exercise equipment be informed of the following information prior to its use.

Do not use any equipment in any way other than designed or intended by the manufacturer. It is imperative that MATRIX equipment be used properly to avoid injury.

## INSTALLATION

1. **STABLE AND LEVEL SURFACE:** MATRIX exercise equipment must be installed on a stable base and properly leveled.
2. **SECURING EQUIPMENT:** **Manufacturer recommends that all stationary MATRIX strength equipment be secured to the floor to stabilize equipment and eliminate rocking or tipping over. This must be performed by a licensed contractor.**
3. Under no circumstances should you slide equipment across the floor due to risk of tipping. Use proper materials handling techniques and equipment recommended by OSHA.

All anchor points must be able to withstand 750 lbs. (3.3 kN) pull-out force.

## MAINTENANCE

1. **DO NOT** use any equipment that is damaged and or has worn or broken parts. Use only replacement parts supplied by your country's local MATRIX dealer.
2. **MAINTAIN LABELS AND NAMEPLATES:** Do not remove labels for any reason. They contain important information. If unreadable or missing, contact your MATRIX dealer for a replacement.
3. **MAINTAIN ALL EQUIPMENT:** Preventative maintenance is the key to smooth operating equipment as well as keeping your liability to a minimum. Equipment needs to be inspected at regular intervals.
4. Ensure that any person(s) making adjustments or performing maintenance or repair of any kind is qualified to do so. MATRIX dealers will provide service and maintenance training at our corporate facility upon request.

## ADDITIONAL NOTES

This equipment should only be used in supervised areas where access and control is specifically regulated by the owner. It is up to the owner to determine who is allowed access to this training equipment. The owner should consider a user's: degree of reliability, age, experience, etc.

This training equipment meets industry standards for stability when used for its intended purpose in accordance with the instructions provided by the manufacturer.

This equipment is for indoor use only. This training equipment is designed for use in a commercial environment such as a fitness facility. Platforms may slide if placed on the following surfaces: Turf, concrete, tile, linoleum.

## UNPACKING

Thank you for purchasing a MATRIX Fitness product. It is inspected before it is packaged. It is shipped in multiple pieces to facilitate the compact packaging of the machine. Prior to assembly, confirm all the components by matching them with the exploded diagrams. Carefully unpack the unit from this box and dispose of the packing materials in accordance with your local laws. Exercise device must be assembled by a trained assembly team or be pre-assembled prior to delivery.

## CAUTION

To avoid injury to yourself and prevent damage to the frame components, be sure to have proper assistance removing the frame pieces from this box. Please be sure to install the equipment on a stable base, and properly level the machine. Ensure a minimum clearance width of 0.6 meters (24") for access to and passage around MATRIX strength equipment. Please note, 0.91 meters (36") is the ADA recommended clearance width for individuals in wheelchairs.



# PRODUCT INFORMATION

## PRODUCT SPECIFICATIONS

	Overall Dimensions (L x W x H) *						Product Weight		Max Training		Max User	
	CM		IN				KG	LBS	KG	LBS	KG	LBS
MG-MX47P-08	390	254	7	153.5	100	2.6	287	633	408.5	900	181.5	400
MG-MX47P-4-08	329	254	7	129.5	100	2.6	224	494	408.5	900	181.5	400
MG-MX47P-CPH-08	366.5	254	7	144.5	100	2.6	278	613	408.5	900	181.5	400
MG-MX47P-CPH-4-08	306	254	7	120.5	100	2.6	215	474	408.5	900	181.5	400
MG-MX690P-08	333.5	254	7	131.5	100	2.6	266	587	408.5	900	181.5	400
MG-MX690P-4-08	273	254	7	107.5	100	2.6	203	448	408.5	900	181.5	400
MG-MX691P-08	318.5	254	7	125.5	100	2.6	260.5	575	408.5	900	181.5	400
MG-MX691P-4-08	258	254	7	101.5	100	2.6	197	435	408.5	900	181.5	400
MG-MXRP47-06	390	254	7	153.5	100	2.6	324.5	716	408.5	900	181.5	400
MG-MXRP47-4-06	329	254	7	129.5	100	2.6	247.5	546	408.5	900	181.5	400
MG-MXRP47-CPH-06	366.5	254	7	144.5	100	2.6	314	693	408.5	900	181.5	400
MG-MXRP47-CPH-4-06	306	254	7	120.5	100	2.6	237	523	408.5	900	181.5	400
MG-MXRP690-06	333.5	254	7	131.5	100	2.6	298.5	658	408.5	900	181.5	400
MG-MXRP690-4-06	273	254	7	107.5	100	2.6	222	490	408.5	900	181.5	400
MG-MXRP691-06	318.5	254	7	125.5	100	2.6	291.5	643	408.5	900	181.5	400
MG-MXRP691-4-06	258	254	7	101.5	100	2.6	215	474	408.5	900	181.5	400

\* Ensure a minimum clearance width of 0.6 meters (24") for access to and passage around MATRIX strength equipment. Please note, 0.91 meters (36") is the ADA recommended clearance width for individuals in wheelchairs.

## MAINTENANCE CHECKLIST

ACTION	FREQUENCY
Inspect Hardware	Monthly
Inspect Frame	Bi-Annually
Clean Platform <sup>1</sup>	As Needed

<sup>1</sup> Hardwood: Use hardwood cleaner.  
Rubber: Use Taski Profi cleaner

## TORQUE VALUES

½ - 13" Bolt (Nyloc Nut & Flowdrill)	135 Nm / 100 ft-lbs.
¾ - 16" Bolt (Nyloc Nut & Flowdrill)	77 Nm / 57 ft -lbs.
5/16 - 18" Bolts	25 Nm / 18 ft-lbs.
5/16 - 18" Plastic	15 Nm / 11 ft-lbs.
¼ - 20" Bolts	15 Nm / 11 ft-lbs.
Pad Bolts	10 Nm / 7 ft-lbs.

## PROPER USAGE



1. Do not exceed weight limits of the exercise device.
2. If applicable, set safety stops to appropriate height.
3. If applicable, adjust seat pads, leg pads, foot pads, range of motion adjustment, or any other type of adjustment mechanisms to a comfortable start position. Make certain that the adjusting mechanism is fully engaged to prevent unintentional movement and to avoid injury.
4. Sit on bench (if applicable) and get into appropriate position for exercise.
5. Exercise using no more weight than you can safely lift and control.
6. In a controlled manner, perform exercise.
7. Return weight to its fully-supported start position.

## WARRANTY

For North America, please visit [matrixfitness.com](http://matrixfitness.com) for warranty information along with warranty exclusions and limitations.



# PRODUCT INFORMATION






# ASSEMBLY

## HARDWOOD PLATFORMS


- MG-MX47P-08
- MG-MX47P-4-08
- MG-MX47P-CPH-08
- MG-MX47P-CPH-4-08
- MG-MX690P-08
- MG-MX690P-4-08
- MG-MX691P-08
- MG-MX691P-4-08




**1**



2	Hardware	Qty
A	Hex Bolt (5/16-16 x 1" Zinc)	4
B	Washer (5/16" Zinc)	4
C	Flange Bolt (5/16-18 x 1" Black Zinc)	4




3	Hardware	Qty
C	Flange Bolt (5/16-18 x 1" Black Zinc)	12



Assemble one corner at a time and work clockwise around the frame, checking dimensions as you go. Make sure the rails form a perfect rectangle before beginning the next step.

# ASSEMBLY


4	Hardware	Qty
D	Bolt (1/4-20 x 2" Bronze)	3




Important: Pay careful attention to the alignment of the hardwood inserts and the rails. The seam of the hardwood inserts must align exactly with (or be slightly recessed from) the inside edges of the rails.

The rack's rear brace is slotted and can be adjusted (adjustment points marked above) to move the hardwood insert further backward or forward.


5	Hardware	Qty
E	Screw (#6 x 1 1/2")	10



## 6



On starting side, make sure Flange Bolts are centered in slots before measuring 95 7/8" (2435 mm) to secure the opposite side.




Starting side: Flange Bolt centered in slot

Inside edge to inside edge of the front and back rails:

4' models: 48 1/8" (1222 mm)  
6' models: 71 7/8" (1826 mm)

Optional bolt-down kits are available.

Install the optional bolt-down brackets on the front and back rails. Do not install them on the sides.



**ASSEMBLY COMPLETE**




# ASSEMBLY

## RUBBER PLATFORMS


- MG-MXRP47-06
- MG-MXRP47-4-06
- MG-MXRP47-CPH-06
- MG-MXRP47-CPH-4-06
- MG-MXRP690-06
- MG-MXRP690-4-06
- MG-MXRP691-06
- MG-MXRP691-4-06




**1**




2	Hardware	Qty
A	Hex Bolt (5/16-16 x 1" Zinc)	4
B	Washer (5/16" Zinc)	4
C	Flange Bolt (5/16-18 x 1" Black Zinc)	4




3	Hardware	Qty
D	Screw (#6 x 1 1/8")	3




4	Hardware	Qty
D	Screw (#6 x 1 1/8")	10




5	Hardware	Qty
C	Flange Bolt (5/16-18 x 1" Black Zinc)	12



**6**



**ASSEMBLY COMPLETE**



# MATRIX



**MAGNUM MX PLATFORMS**

© 2025 Johnson Health Tech

Rev 1.1 A